


2400/2420 ENKODERY INKREMENTALNE

SERIE 2400

- Mała obudowa Ø 24 mm
- Kabel 2m
- Szeroki zakres temperatur (-20° do +85°C)
- Maksymalna rozdzielczość 1024 impulsów/obrot



OPIS PRODUKTU

Seria enkoderów inkrementalnych do zastosowań przemysłowych, gdzie jest mało miejsca lub czujnik musi być lekki. Dostępne w dwóch rozmiarach obudowy. Seria 2400/2420 posiada wyjście Push-pull, co oznacza, że można go podłączyć do wejść PNP lub NPN. Sygnałami wyjściowymi są A, B, 0. Sygnały znegowane pozwalają na podłączenie do wejść przystosowanych do eliminacji zakłóceń.

W celu określenia numeru katalogowego proszę o zapoznanie się z poniższymi informacjami.

Order code Shaft version	05.2400 Type	. XX XX . XXXX		
a Flange 1 = $\varnothing$ 24 mm [0.94"] 3 = $\varnothing$ 28 mm [1.10"] 2 = $\varnothing$ 30 mm [1.18"]	c Output circuit / power supply 1 = push-pull (without inverted signal) / 5 ... 24 V DC 2 = push-pull (with inverted signal) / 5 ... 24 V DC 3 = push-pull (without inverted signal) / 8 ... 30 V DC 4 = push-pull (with inverted signal) / 8 ... 30 V DC	d Type of connection 1 = axial cable, 2 m [6.56'] PVC A = axial cable, special length PVC *) 2 = radial cable, 2 m [6.56'] PVC B = radial cable, special length PVC *) *) Available special lengths (connection types A, B): 3, 5, 8, 10, 15 m [9.84, 16.40, 26.25, 32.80, 49.21'] order code expansion .XXXX = length in dm ex.: 05.2400.122A.1024.0030 (for cable length 3 m)	e Pulse rate 4, 6, 8, 10, 16, 20, 25, 36, 40, 50, 60, 80, 100 , 120, 125, 180, 200, 250, 300, 360 , 400, 500, 512 , 1000 , 1024 (e.g. 360 pulses => 0360)	Stock types 05.2400.1122.0050 05.2400.1122.0360 05.2400.1122.0500 05.2400.1122.1000 05.2400.1122.1024 Optional on request - other pulse rates

Order code Hollow shaft		05.2420 Type	1	X	X	X	XXXX
			a	b	c	d	e
a Flange							
1 = ø 24 mm [0.94"]							
b Blind hollow shaft							
(insertion depth max. 14 mm [0.55"])							
1 = ø 4 mm [0.16"]							
2 = ø 6 mm [0.24"]							
4 = ø 1/4" ¹⁾							