

SERIA AR


AR1-610-24-B-A-3-3-312

- 1 - 6-polowe
- 0.1-50 A
- Do 277 V AC
- Do 90 V DC



OPIS PRODUKTU

Firma Mors Smitt ze względu na swoje świetne zorientowanie na potrzeby klienta oferuje szeroką gamę wyłączników miniaturowych o przeróżnych specyfikacjach, aby sprostać najwyższym wymaganiom. Zamówienia należy komponować zgodnie z poniższą formatką. Przedstawione produkty są przykładowe.



1 Series

AR

2 Poles

1 One	4 Four
2 Two	5 Five
3 Three	6 Six

3 Current rating (amperes)

210 0.100	512 1.250	485 8.500
215 0.150	415 1.500	490 9.000
220 0.200	517 1.750	495 9.500
225 0.250	420 2.000	499 10.000
230 0.300	522 2.250	435 15.000
235 0.500	423 3.500	434 16.000
240 0.600	527 2.750	437 17.000
245 0.450	430 3.000	438 18.000
250 0.500	435 3.500	420 20.000
260 0.600	440 4.000	422 22.000
265 0.650	445 4.500	424 24.000
270 0.700	450 5.000	425 25.000
275 0.750	455 5.500	430 30.000
280 0.800	460 6.000	435 35.000
285 0.850	465 6.500	440 40.000
290 0.900	470 7.000	450 50.000
295 0.950	475 7.500	
410 1.000	480 8.000	

Or voltage coil (nominal and voltage)

306 6 DC	56 6 AC
312 12 DC	12 12 AC
318 18 DC	18 18 AC
324 24 DC	24 24 AC
332 32 DC	32 32 AC
344 44 DC	44 44 AC
365 65 DC	65 65 AC

Other values on request

4 Frequency & delay

01 DC, 50/60 Hz, switch only
10 DC instantaneous
11 DC ultra short
12 DC short
14 DC, medium
16 DC long
20 50/60 Hz instantaneous
21 50/60 Hz ultra short
22 50/60 Hz short
24 50/60 Hz medium
26 50/60 Hz long
42 50/60 Hz short, hi-inrush
44 50/60 Hz medium, hi-inrush
46 50/60 Hz long, hi-inrush
52 DC, short, hi-inrush
54 DC, medium, hi-inrush
56 DC, long, hi-inrush

5 Circuit

A ¹ Switch only (no coil)
B Series trip (current)
C Series trip (voltage)
D Shunt trip (current)
E ² Shunt trip (voltage)
3H ³ Dual coil with shunt trip voltage coil

6 Actuator¹

A Handle, one per pole
B Handle, one per multipole unit
S Mid-trip handle, one per pole
T Mid-trip handle, one per pole & alarm switch

7 Actuator colour & legend

Actuator colour	I-O	ON-OFF	Dual	Legend colour
White	A	B	1	Black
Black	C	D	2	White
Red	E	G	3	White
Green	H	J	4	White
Blue	K	L	5	White
Yellow	M	N	6	Black
Grey	P	Q	7	Black
Orange	R	S	8	Black
White (short handle) ²	V	W	0	Black

8 Auxiliary switch³

0 Without auxiliary switch
2 SPDT, 0.110 QC, term.
3 SPDT, 0.139 solder lug
4 SPDT, 0.110 QC, term. (gold contacts)
A SPDT, 0.110 QC, term. with mounted cover
B SPDT, 0.110 QC, term. (gold contacts) with mounted cover

9 Terminal¹⁰

1 ¹¹ Push-on, 0.250 tab (Q.C.)
2 Screw 8-32 with upturned lugs
3 ¹² Screw 8-32 (bus type)
4 Screw 10-32 with upturned lugs
5 ¹³ Screw 10-32 (bus type)
6 Screw 8-32 with upturned lugs and 30° bend
7 ¹⁴ Screw 8-32 (bus type) and 30° bend
8 Screw 10-32 with upturned lugs and 30° bend
9 ¹⁵ Screw 8-32 (bus type) and 30° bend
B Screw M5 with upturned lugs
C Screw M4 with upturned lugs
E ¹⁶ Screw M4 (bus type)
F Screw M5 with upturned lugs and 30° bend
G ¹⁷ Screw M5 (bus type) and 30° bend
H ¹⁸ Screw M5 (bus type)
M ¹⁹ M6 threaded stud
Q Push-in stud
R Screw M4 with upturned lugs and 30° bend
T Screw M4 (bus type) and 30° bend
U Double lumen 0.25" / 6,3 mm
V M6 threaded stud 17 mm long with NTF washers and nut

Notes:

- Available up to two poles with AC or DC delays
- Separate pole type voltage coils not rated for continuous duty. Available only with delay codes 10, 20 & 30
- Available with circuit codes B & D only
- For 0.1 - 30 A: select current code 630
- For 35 - 50 A: select current code 650
- Available with terminal codes 1, 2 & 3. Current rating limited to 30 A maximum
- Consult Mors Smitt for available dual coil options, a special catalogue number is required. With shunt construction, dual coils will trip instantaneously on line voltage. Dual coils require 30 VA minimum power to trip and are rated for intermittent duty only
- Actuator code:
 - S: Handle moves to mid-position only upon electrical trip of the breaker, available with all circuit codes, except switch only
 - T: Handle moves to mid-position and alarm switch activates only upon electrical trip of the breaker, available with circuit codes B & C
- Single pole only
- On multi-pole breakers, one auxiliary switch is supplied, mounted in the extreme right pole (rear view)
- Rated over 30 A are only available with terminals codes 5, 9, G and H
- Terminal code 1: up to 30 A, but not recommended over 20 A
- Terminal codes 3, 5, 7, 9, E, G and H (bus type) are supplied with lock washers
- Terminal code M (M6 threaded stud) is supplied with lock and flat washers
- TUV certified: not for switch only circuits and only for actuator legend 'S-O' and dual legend
- UL recognized: for most applications, not all
- Special applications without appendix: agency approval code A

10 Mounting & barriers

Mounting style	Barriers
flushed insert, 2 per pole	No
1 6-32 x 0.195 inch	No
A 6-32 x 0.195 inch	Yes (between poles only)
2 ISO M3 x 5 mm	No
B ISO M3 x 5 mm	Yes (between poles only)

12 Agency approval

2 ²⁰ TUV certified, UL recognized
--

Wszystkie wyłączniki firmy Mors Smitt są projektowane zgodnie z normami:

- IEC 60077-1/2/3/4
- NF F62-001 - 1/2/3
- NF F16-101/102
- EN 45545-2
- EN 50155
- EN 61373
- EN 50124-1
- IEC 60068-2-30
- IEC 60068-2-52
- NF F61-010