

EM-240

Sterownik silników BLDC

EM-240

Sterownik silnika BLDC, 4Q, 12-24V DC, 1.5A

- 12-24 V DC, 1.5 A prąd ciągły, 2 A prąd szczytowy
- Praca w pętli otwartej lub zamkniętej (sprężenie zwrotne z czujników Halla)
- Praca czterokwadrantowa
- Nastawa parametrów poprzez przełączniki
- Kompaktowa budowa, montaż na szynie DIN



OPIS PRODUKTU

EM-240 controller is designed for small brushless DC-motors. The unit is suitable for three phase hall transducer brushless motors. There are two operating modes: in open loop operating mode the motor voltage is proportional to control value with the characteristics of a common DC-motor with brushes. In closed loop operation hall transducer signal is used to regulate motor speed. Through the feedback, a precise motor rpm in relation to control value can be achieved.

The motor operating speed and running direction can be adjusted and the motor may be braked in both operating modes. The power stage uses PWM principle and is highly efficient.

Speed control value is given as analog voltage signal. The auxiliary voltage signal is regulated and may be used as reference value for control potentiometer. The acceleration speed can be adjusted with acceleration and deceleration ramp. Deceleration ramp can also be bypassed when rapid braking is desired. Additionally the unit is equipped with speed2-feature, which can be activated individually. This is especially practical in positioning applications.

Current limit can be used to restrict motor torque and is dip-switch settable. Control inputs work with positive (NPN) logic. EM-170 is EMC-tested in accordance with industrial standards.

FEATURES:

- Hall sensor supply and input
- Open or closed loop activity
- Controlled direction change
- Braking
- Settable current limit
- Settable start and stop ramp
- Dip-switch settable
- EMC tested

SPECYFIKACJA TECHNICZNA

2421_Peak current (A)	2
5646_Dimensions length x width x height (mm)	60x60x20 mm
Częstotliwość PWM	16kHz
Dostawca	Electromen
Maksymalny prąd ciągły	1.5 A
Masa	30 g
Montaż	szyna DIN
Napięcie zasilania	12 V DC, 24 V DC

Odpowiedni silnik

Bezszczotkowy DC

Rodzaj sterowania

Prędkość, Hamowanie, Kierunek, Moment, Soft start/stop

Sygnal niski - logiczne 0

<1V = OFF

Sygnal wysoki - logiczne 1

>4V = ON

Temperatura pracy

0°C...+60°C

Wejście analogowe

0-10V

Zakres ustawień prądu

0.2-2 A

