

SERIA FR

FR3-810-26-B-S-A-9-1-A

- 1 - 3-polowe
- 100-700 A
- Do 277 V AC
- Do 137.5 V DC



OPIS PRODUKTU

Firma Mors Smitt ze względu na swoje świetne zorientowanie na potrzeby klienta oferuje szeroką gamę wyłączników miniaturowych o przeróżnych specyfikacjach, aby sprostać najwyższym wymaganiom. Zamówienia należy komponować zgodnie z poniższą formatką. Przedstawione produkty są przykładowe.

Ordering scheme FR - page 1

FR			code continues on following page.....
Poles	1	1 pole	
	2	2 poles	
	3	3 poles	
Current rating (amperes) ¹	810	100.0	
	812	120.0	
	912	125.0	
	815	150.0	
	917	175.0	
	820	200.0	
	922	225.0	
	825	250.0	
	830 ¹⁴	300.0	
	835 ¹⁴	350.0	
	840 ¹⁴	400.0	
	845 ¹⁴	450.0	
	850 ¹⁴	500.0	
	860 ¹⁴	600.0	
	870 ¹⁴	700.0	
Frequency & delay	11	DC ultra short	
	12	DC short	
	14	DC medium	
	16	DC long	
	22	50/60 Hz short	
	24	50/60 Hz medium	
	26	50/60 Hz long	

Ordering scheme FR - page 2

.....			
Circuit	B	Single pole or multi-pole (max. 250 A) - Series trip (current)	
	P ¹	Parallel pole construction (300 A - 700 A) - Series trip (current)	
Actuator ²	A	Handle, one per pole	
	S	Mid-trip handle, one per pole	
	T	Mid-trip handle, one per pole & alarm switch	
	..		
Actuator colour & legend	..		
Auxiliary switch ³	0	Without auxiliary switch	
	2	S.P.D.T., 0.110 QC terminals	
	3	S.P.D.T., 0.139 solder lug	
	4	S.P.D.T., 0.110 QC terminals (gold contacts)	
	9	S.P.D.T., 0.187 QC terminals	
	B ⁴	S.P.D.T., 0.093 round QC terminals	
Terminal	1 ⁵	Back connected (front mounted only)	
	2 ⁶	Stud 3/8-16, max. rating 250 A	
	5 ⁶	Screw, line & load 3/8-16, max. rating 700 A	
		Short stud 3/8-16, max. rating 250 A	
	3	Front connected (back mounted only) ⁷	
	4 ⁶	Box wire connector, line & load, max. rating 700 A	
		Screw, line & load 3/8-16, max. rating 700 A	
Mounting	A	Front mounting inserts ¹² : 10-32, back mouting inserts 10-32 screw clearance holes	
	B	Front mounting inserts ¹² : ISO M5, back mouting inserts 10-32 screw clearance holes	
Maximum application rating	B	125 VDC, 700 A	
	C ⁸	120/240 VAC, 250 A	
	F	277 VAC, 250 A	
	7 ⁹	120/208 VAC, 250 A	
Agency approval	A	No aproval ¹⁰	

Wszystkie wyłączniki firmy Mors Smitt są projektowane zgodnie z normami:

- IEC 60077-1/2/3/4
- NF F62-001 - 1/2/3
- NF F16-101/102
- EN 45545-2
- EN 50155
- EN 61373
- EN 50124-1
- IEC 60068-2-30
- IEC 60068-2-52
- NF F61-010