

SENDIX F5868/5888, OPTYCZNY, WIELOBROTOWY, ETHERNET/IP, Ø58 MM

Enkodery wielobrotowe absolutne optyczne

SERIE F5868 ETHERNET/IP

- Średnica zewnętrzna: Ø 58 mm
- Maks. średnica wałka: Ø 10 mm. Maks. średnica otworu: Ø 15 mm
- Maks. rozdzielczość: 16 bitów ST + 16 bitów MT
- EtherNet/IP
- Safety-Lock™



OPIS PRODUKTU

Sendix F5868 / F5888 is a multivalued fieldbus transducer with EtherNet / IP in robust design. Thanks to the construction of Safety-Lock™ as well as the fully cast housing, the sensor is able to handle even the more demanding applications where there are high demands on the sensor. The wide temperature range combined with the high enclosure class allows the sensor to be used outdoors as well as applications where large temperature changes occur. Sendix F5868 / F5888 comes with LED indication which facilitates diagnosis of the sensor.

W celu określenia numeru katalogowego proszę o zapoznanie się z poniższymi informacjami.

Order code Shaft version	8.F5868 . XXAN . A2 2 2				
	Type	a	b	c	d
a Flange		b Shaft (ø x L), with flat		c Interface / Power supply	d Fieldbus profile
1 = clamping flange, IP65 ø 58 mm [2.28"]		1 = 6 x 10 mm [0.24 x 0.39"]		A = EtherNet IP / 10 ... 30 V DC	A2 = EtherNet/ IP
2 = synchro flange, IP65 ø 58 mm [2.28"]		2 = 10 x 20 mm [0.39 x 0.79"]			
5 = square flange, IP65 □ 63.5 mm [2.5"]		3 = 1/4" x 7/8"		d Type of connection	Optional on request
		4 = 3/8" x 7/8"		N = 3 x axial M12 connector, 4-pin	- Ex 2/22

Order code Hollow shaft	8.F5888 . XXAN . A2 2 2				
	Type	a	b	c	d
a Flange		b Blind hollow shaft		c Interface / Power supply	d Fieldbus profile
1 = with spring element long, IP65		(insertion depth max. 30 mm [1.18"])		A = EtherNet IP / 10 ... 30 V DC	A2 = EtherNet/ IP
3 = with stator coupling, IP65 ø 65 mm [2.56"]		A = ø 10 mm [0.39"]			
5 = with stator coupling, IP65 ø 63 mm [2.48"]		B = ø 12 mm [0.47"]		d Type of connection	Optional on request
		C = ø 14 mm [0.55"]		N = 3 x axial M12 connector, 4-pin	- Ex 2/22
		D = ø 15 mm [0.59"]			
		E = ø 3/8"			
		F = ø 1/2"			

SPECYFIKACJA TECHNICZNA

Max. temperatura pracy	80 °C
Min. temperatura pracy	-40 °C
Montaż	Wał
Napięcie zasilania DC max.	30 V DC
Napięcie zasilania DC min.	10 V DC
Podłączenie	Złącze M12
Rozdzielczość MT	Max. 16 bit
Średnica obudowy	58 mm
Średnica wału max	10 mm
Średnica wału min	6 mm
Stopień ochrony IP	IP65
Typ czujnika	Absolutny
Wersja	Wielobrotowy
Wyjście	EtherNet/IP

