


2400/2420 ENKODERY INKREMENTALNE

2400.1122.0500

- Mała obudowa Ø 24 mm
- Kabel 2m
- Szeroki zakres temperatur (-20° do +85°C)
- Maksymalna rozdzielczość 1024 impulsów/obrót



OPIS PRODUKTU

Seria enkoderów inkrementalnych do zastosowań przemysłowych, gdzie jest mało miejsca lub czujnik musi być lekki. Dostępne w dwóch rozmiarach obudowy. Seria 2400/2420 posiada wyjście Push-pull, co oznacza, że można go podłączyć do wejść PNP lub NPN. Sygnałami wyjściowymi są A, B, 0. Sygnały znegowane pozwalają na podłączenie do wejść przystosowanych do eliminacji zakłóceń.

W celu określenia numeru katalogowego proszę o zapoznanie się z poniższymi informacjami.

Order code Shaft version	05.2400 . XXXXX . XXXX Type
a Flange 1 = ø 24 mm [0.94"] 3 = ø 28 mm [1.10"] 2 = ø 30 mm [1.18"] b Shaft ($\phi \times L$) 1 = ø 4 x 10 mm [0.16 x 0.39"] 3 = ø 5 x 10 mm [0.20 x 0.39"], with flat 2 = ø 6 x 10 mm [0.24 x 0.39"] 4 = ø 1/4" x 10 mm [1/4" x 0.39"], with flat ⁽¹⁾ 6 = ø 6 x 10 mm [0.24 x 0.39"], with flat ⁽¹⁾	c Output circuit / power supply 1 = push-pull (without inverted signal) / 5 ... 24 V DC 2 = push-pull (with inverted signal) / 5 ... 24 V DC 3 = push-pull (without inverted signal) / 8 ... 30 V DC 4 = push-pull (with inverted signal) / 8 ... 30 V DC d Type of connection 1 = axial cable, 2 m [6.56'] PVC A = axial cable, special length PVC *) 2 = radial cable, 2 m [6.56'] PVC B = radial cable, special length PVC *) *) Available special lengths (connection types A, B): 3, 5, 8, 10, 15 m [9.84, 16.40, 26.25, 32.80, 49.21'] order code expansion .XXXX = length in dm ex.: 05.2400.122A.1024.0030 (for cable length 3 m)

Order code Hollow shaft		05.2420 Type		1		X		X		X		XXXX	
				a		b		c		d		e	
a Flange													
1 = ø 24 mm [0.94"]													
b Blind hollow shaft (insertion depth max. 14 mm [0.55"])													
1 = ø 4 mm [0.16"]													
2 = ø 6 mm [0.24"]													
4 = ø 1/4" ¹⁾													