

SENDIX 5868/5888, OPTYCZNY, WIELOBROTOWY, PROFIBUS, Ø58 MM

Enkodery wielobrotowe absolutne optyczne

SERIE 5868 PROFIBUS



- Średnica zewnętrzna: Ø 58 mm
- Maks. średnica wałka: Ø 10 mm. Maks. średnica otworu: Ø 15 mm
- Maks. rozdzielczość: 16 bitów ST + 12 bitów MT
- Profibus
- Safety-Lock™



OPIS PRODUKTU

Sendix 5868/5888 is a multivariate fieldbus sensor with Profibus in robust design. Thanks to the construction of Safety-Lock™ as well as the fully cast housing, the sensor is able to handle even the more demanding applications where there are high demands on the sensor. The wide temperature range combined with the high enclosure class allows the sensor to be used outdoors as well as applications where large temperature changes occur. Sendix 5868/5888 has LED indication which facilitates diagnosis of the sensor and a set button that facilitates calibration.

W celu określenia numeru katalogowego proszę o zapoznanie się z poniższymi informacjami.

Order code		8.5868		.XX3X		.311X		
Shaft version		Type	a	b	c	d	e	f
a Flange	1 = clamping flange, IP65 ø 58 mm [2.28"] 3 = clamping flange, IP67 ø 58 mm [2.28"]	3 = PROFIBUS DP V0 encoder profile V 1.1, 10 ... 30 V DC	d Type of connection, removable bus terminal cover		e Fieldbus profile		31 = PROFIBUS DP V0 encoder profile class 2	
2 = synchro flange, IP65 ø 58 mm [2.28"] 4 = synchro flange, IP67 ø 58 mm [2.28"] 5 = square flange, IP65 □ 63.5 mm [2.5"] 7 = square flange, IP67 □ 63.5 mm [2.5"]	1 = with radial cable gland fitting 2 = with 3 x radial M12 connectors	f Options (service)		2 = no option 3 = SET button				
b Shaft (ø x L), with flat	1 = 6 x 10 mm [0.24 x 0.39"]¹⁾ 2 = 10 x 20 mm [0.39 x 0.79"]²⁾ 3 = 1/4" x 7/8" 4 = 3/8" x 7/8"	Optional on request		- Ex 2/22 - surface protection salt spray tested - seawater resistant (stainless steel V4A)				
		Salt spray tested / stainless steel V4A as standard types (deliverable as from 1 unit)		salt spray tested: 8.5868.3232.3112-C		stainless steel V4A: 8.5868.3232.3112-V4A		
								

Order code
Hollow shaft

8.5888
Type

. X X 3 X . 31 1 X
a b c d e f

a Flange

- 1 = with spring element, long, IP65
- 2 = with spring element, long, IP67
- 3 = with stator coupling, IP65 ø 65 mm [2.56"]
- 4 = with stator coupling, IP67 ø 65 mm [2.56"]
- 5 = with stator coupling, IP65 ø 63 mm [2.48"]**
- 6 = with stator coupling, IP67 ø 63 mm [2.48"]

b Blind hollow shaft

(insertion depth max. 30 mm [1.18"])

- 3 = ø 10 mm [0.39"]
- 4 = ø 12 mm [0.47"]**
- 5 = ø 14 mm [0.55"]
- 6 = ø 15 mm [0.59"]
- 8 = ø 3/8"
- 9 = ø 1/2"

c Interface / power supply

3 = PROFIBUS DP V0 encoder profile V 1.1, 10 ... 30 V DC

d Type of connection, removable bus terminal cover

- 1 = with radial cable gland fitting
- 2 = with 3 x radial M12 connectors**

e Fieldbus profile

31 = PROFIBUS DP V0 encoder profile class 2

f Options (service)

- 2 = no option
- 3 = SET button**

Optional on request

- Ex 2/22
- surface protection salt spray tested
- seawater resistant (stainless steel V4A)

Salt spray tested / stainless steel V4A as standard types (deliverable as from 1 unit)





salt spray tested:
8.5888.2432.3112-C
8.5888.2532.3112-C






stainless steel V4A:
8.5888.2432.3112-V4A

SPECYFIKACJA TECHNICZNA

Max. temperatura pracy	80 °C
Min. temperatura pracy	-40 °C
Montaż	Wał
Napięcie zasilania DC max.	30 V DC
Napięcie zasilania DC min.	10 V DC
Podłączenie	Kabel, Złącze M12
Resolution Overall	Max. 28 bit (default 25 bit)
Rozdzielczość MT	12 bit
Rozdzielczość ST	16 bit (default: 13 bit)
Średnica obudowy	58 mm
Średnica wału max	10 mm
Średnica wału min	6 mm
Stopień ochrony IP	IP65, IP67
Typ czujnika	Absolutny
Wersja	Wielobrotowy
Wyjście	Profibus



Interface	Type of connection	Signal Terminal	BUS IN					BUS OUT					The shield of the connection cable must be connected near or larger area via the cable gland.		
			0	A	±V	±V	±V	0	A	±V	±V	±V			
3	6 (terminal box)	1 2 3 4 5 6 7 8													
3	2 (3 x M12 connector)	Bus In	Signal	-	PB A	-	PB B	Shield							
		Power supply	Signal	+V	-	±V	-								
		Bus out	Signal	0V	0V	0V	0V	0V	0V	0V	0V	0V	0V	0V	0V
		Pin	1	2	3	4	5	6	7	8	9	10	11	12	13

Interface	Type of connection	BUS IN					BUS OUT			The shield of the connection cable must be connected near a large area on the cable gland.	
		Signal	B	A	DV	+V	DV	+V	B		A
3	1 (terminal box)	Signal	1	2	3	4	5	6	7	8	
		Terminal	1	2	3	4	5	6	7	8	
Interface	Type of connection	Function	Signal		PB A		PB B		Shield		
			Pin	Pin	Pin	Pin	Pin	Pin			
3	2 (3 x M12 connector)	Bus in	Signal	-							
			Pin	1	2	3	4	5			
		Power supply	Signal	+V	-	DV	-				
			Pin	1	2	3	4				
		Bus out	Signal	BUS OUT	PB A	BUS OUT	PB B	Shield			
			Pin	1	2	3	4	5			