

SENDIX 5868/5888, OPTYCZNY, WIELOBROTOWY, PROFINET, Ø58 MM

Enkodery wielobrotowe absolutne optyczne

SERIE 5888 PROFINET

- Średnica zewnętrzna: Ø 58 mm
- Maks. średnica wałka: Ø 10 mm. Maks. średnica otworu: Ø 15 mm
- aks. rozdzielczość: 16 bitów ST + 12 bitów MT
- PROFINET IO
- Safety-Lock™



OPIS PRODUKTU

Sendix 5868/5888 is a multivariate sensor with Profinet in robust design. Thanks to the construction of Safety-Lock™ as well as the fully cast housing, the sensor is able to handle even the more demanding applications where there are high demands on the sensor. The wide temperature range combined with the high enclosure class allows the sensor to be used outdoors as well as applications where large temperature changes occur.

W celu określenia numeru katalogowego proszę o zapoznanie się z poniższymi informacjami.

Order code	8.5868	.XXC2.C212		
Shaft version	Type	a b c d e		
a Flange	b Shaft (ø x L), with flat	c Interface / power supply	d Type of connection	e Fieldbus profile
1 = clamping flange, IP65 ø 58 mm [2.28"]	1 = 6 x 10 mm [0.24 x 0.39"] ¹⁾	C = PROFINET IO / 10 ... 30 V DC	removable bus terminal cover	C2 = PROFINET IO
3 = clamping flange, IP67 ø 58 mm [2.28"]	2 = 10 x 20 mm [0.39 x 0.79"] ²⁾			Optional on request
2 = synchro flange, IP65 ø 58 mm [2.28"]	3 = 1/4" x 7/8"		2 = 3 x M12 connector, 4-pin	- Ex 2/22
4 = synchro flange, IP67 ø 58 mm [2.28"]	4 = 3/8" x 7/8"			- surface protection salt spray tested
5 = square flange, IP65 □ 63.5 mm [2.5"]				
7 = square flange, IP67 □ 63.5 mm [2.5"]				

Order code	8.5888	.XXC2.C212		
Hollow shaft	Type	a b c d e		
a Flange	b Blind hollow shaft (insertion depth max. 30 mm [1.18"])	c Interface / power supply C = PROFINET IO / 10 ... 30 V DC	d Type of connection removable bus terminal cover 2 = 3 x M12 connector, 4-pin	e Fieldbus profile C2 = PROFINET IO
1 = with spring element, long, IP65	3 = ø 10 mm [0.39"]			
2 = with spring element, long, IP67	4 = ø 12 mm [0.47"]			
3 = with stator coupling, IP65 ø 65 mm [2.56"]	5 = ø 14 mm [0.55"]			
4 = with stator coupling, IP67 ø 65 mm [2.56"]	6 = ø 15 mm [0.59"]			
5 = with stator coupling, IP65 ø 63 mm [2.48"]	8 = 3/8"			
6 = with stator coupling, IP67 ø 63 mm [2.48"]	9 = 1/2"			
				Optional on request - Ex 2/22 - surface protection salt spray tested

SPECYFIKACJA TECHNICZNA

Max. temperatura pracy	85 °C
Min. temperatura pracy	-40 °C
Montaż	Wał drążony

