

DATALOGIC COMPACT CCD READER TC1200

TC1200-0000
939501110, Scan Engine, CCD reader, RS232

- Maximum Resolution Up To 0.12mm
- Maximum 320 Scans/sec
- Excellent Reading Performance On Bad Label Codes
- Communication Interface RS232/USB.



OPIS PRODUKTU

Thanks to its high-performance CCD sensor, combined with built-in technology for reconstruction of codes, TC1200 can permit fast, correct reading even when the code is damaged or of poor quality. The reader's high immunity to ambient light and its excellent read capacity allows it to be installed in all environments. As a CCD sensor has no moving parts, TC1200 is extremely reliable. The optional mirror, angled 80°, for side installation allows this device to be installed even in enclosed spaces.

SPECYFIKACJA TECHNICZNA

2D kod rozdzielczość max	0,1 mm
Głębina ostrości max.	0,41 m
Interfejs użytkownika	3 LEDs 'Power', 'Good read', 'Trigger' 1 Button for manual triggering
Masa	30 g
Max. temperatura pracy	50 °C
Max. temperatura składowania	70 °C
Min. temperatura pracy	0 °C
Min. temperatura składowania	-20 °C
Odległość odczytu	460 mm
Odporność na światło otoczenia	100.000 LUX
Pobór mocy	1,75 W
Stopień ochrony IP	IP64
Szybkość skanowania	320
Wejścia cyfrowe	1

