

## SILNIK DC Ø32 MM

82860XXX

Silnik 32mmØ 3W 12/24Vdc 3700obr/min 7.7mNm IP40

- Napięcie zasilania 12 lub 24 V DC
- Moment nominalny 7.7 mNm
- Prędkość nominalna 3700 obr/min
- Silnik szczotkowy z magnesami trwałymi
- Wysoki moment startowy



### OPIS PRODUKTU

Standard DC motor range in the 32mmØ size for high speed, lower torque applications.  
The DC motor by nature offers a very high starting torque.

Options for a bespoke solution include, different power connections, EMC filter, encoder options & mechanical/electrical adaptations.

\* Smaller length motor for lower power applications available if required.

### SPECYFIKACJA TECHNICZNA

|                           |                  |
|---------------------------|------------------|
| <b>Długość</b>            | 45 mm            |
| <b>Masa</b>               | 0,096 kg         |
| <b>Moc</b>                | 3 W              |
| <b>Moment startowy</b>    | 0,03             |
| <b>Napięcie zasilania</b> | 12 V DC, 24 V DC |
| <b>Nominalny moment</b>   | 0,0077           |
| <b>Prędkość nominalna</b> | 3700 rpm         |
| <b>Średnica</b>           | 32 mm            |
| <b>Średnica wałka</b>     | 2 mm             |
| <b>Stopień ochrony IP</b> | IP40             |
| <b>Żywotność</b>          | 3000 h           |

