


SENDIX 5006/5026 STAL NIERDZEWNA

SERIE 5006

- Średnica zewnętrzna: Ø 58 mm
- Maks. średnica wałka: Ø 10 mm Maks. średnica otworu: Ø 12 mm
- Maks. rozdzielczość: 5000 imp./obr.
- Wyjście: Push-Pull, RS-422
- Materiał obudowy: stal nierdzewna



OPIS PRODUKTU

Enkodery inkrementalne serii Sendix 5006 / 5026 Kubler wykonane w całości ze stali nierdzewnej zapewniają praktycznie bardzo wysoką trwałość. Wysokiej jakości uszczelki, stopień ochrony IP66 / IP67, jak i szeroki zakres temperatur pracy gwarantują wyjątkową szczelność i odporność.

W celu określenia numeru katalogowego proszę o zapoznanie się z poniższymi informacjami.


Order code Shaft version	8.5006 Type	. XXXX4 . a b c d e	XXXX e
a Flange 7 = clamping flange ø 58 mm [2.28"] A = synchro flange ø 58 mm [2.28"] C = square flange □ 63.5 mm [2.5"]		c Output circuit / power supply 2 = push-pull (7272 compatible with inverted signal) / 5 ... 30 V DC 5 = push-pull (with inverted signal) / 10 ... 30 V DC 4 = RS422 (with inverted signal) / 5 V DC	Optional on request - other pulse rates - Ex 2/22 - seawater resistant (stainless steel V4A)
b Shaft (ø x L), with flat 1 = ø 6 x 10 mm [0.24 x 0.39"] 3 = ø 10 x 20 mm [0.39 x 0.79"] 8 = ø 3/8" x 7/8"		d Type of connection 4 = radial M12 connector, 8-pin	Stainless steel V4A as standard types (deliverable as from 1 unit) 8.5006.73XX4.XXXX-V4A
		e Pulse rate 1, 5, 10, 12, 36, 100, 200, 250, 256, 360, 400, 500, 512, 600, 800, 1000, 1024, 1200, 2000, 2048, 2500, 3600, 4096, 5000 (e.g. 100 pulses => 0100)	V4A 1.4404

Order code Hollow shaft	8.5026 Type	. XXXX2 . a b c d e	XXXX e
a Flange 1 = with spring element, long C = with stator coupling, ø 63 mm		c Output circuit / power supply 2 = push-pull (7272 compatible, with inverted signal) / 5 ... 30 V DC 5 = push-pull (with inverted signal) / 10 ... 30 V DC 4 = RS422 (with inverted signal) / 5 V DC	Optional on request - other pulse rates - Ex 2/22 - seawater resistant (stainless steel V4A)
b Through hollow shaft 2 = ø 1/4" 4 = ø 3/8" 3 = ø 10 mm [0.39"] 5 = ø 12 mm [0.47"] 6 = ø 1/2" 8 = ø 15 mm [0.59"]		d Type of connection 2 = radial M12 connector, 8-pin	Stainless steel V4A as standard types (deliverable as from 1 unit) 8.5026.18XX2.XXXX-V4A
		e Pulse rate 1, 5, 10, 12, 36, 100, 200, 250, 256, 360, 400, 500, 512, 600, 800, 1000, 1024, 1200, 2000, 2048, 2500, 3600, 4096, 5000 (e.g. 100 pulses => 0100)	V4A 1.4404

SPECYFIKACJA TECHNICZNA

Liczba impulsów max	5000
---------------------	------

Montaż	Wał
Napięcie zasilania DC max.	30 V DC
Napięcie zasilania DC min.	5 V DC
Podłączenie	Złącze M12
Średnica obudowy	58 mm
Średnica wału max	10 mm
Średnica wału min	6 mm
Stopień ochrony IP	IP66, IP67
Typ czujnika	Inkrementalny
Wersja	Wielobrotowy
Wyjście	Push/Pull, RS422
Zakres temperatur do	85 °C
Zakres temperatur od	-40 °C



Terminal assignment

Designation	Type of connector	M12 connector, 8-pin
4, A, 1	9000, 4	Signal
5, B, 2	9000, 2	Pin

4/0 Encoder power supply +V DC
 5/0 Encoder power supply ground (GND) (0 V)
 A, A Incremental output channel A
 B, B Incremental output channel B
 0, 0 Reference signal
 Pin A Plug connector housing (shield)

Top view of mating M12, male contact base

