

SILNIK DC Ø32 MM

82860XXX

Silnik 32mmØ 3W 12/24Vdc 3700obr/min 7.7mNm IP40

- Napięcie zasilania 12 lub 24 V DC
- Moment nominalny 7.7 mNm
- Prędkość nominalna 3700 obr/min
- Silnik szczotkowy z magnesami trwałymi
- Wysoki moment startowy



OPIS PRODUKTU

Standard DC motor range in the 32mmØ size for high speed, lower torque applications.
The DC motor by nature offers a very high starting torque.

Options for a bespoke solution include, different power connections, EMC filter, encoder options & mechanical/electrical adaptations.


* Smaller length motor for lower power applications available if required.

SPECYFIKACJA TECHNICZNA

Długość	45 mm
Masa	0,096 kg
Moc	3 W
Moment nominalny	0,0077 Nm
Moment startowy	0,03 Nm
Napięcie zasilania	12 V DC, 24 V DC
Prędkość nominalna	3700 rpm
Średnica	32 mm
Średnica wałka	2 mm
Stopień ochrony IP	IP40
Żywotność	3000 h


Dimensions

With encoder



- 1 2 tags NFC 20 - 120; series 2.8 x 0.5
- 2 3 holes at 120° over Ø 26 mm; use self-tapping M2.2 screws; screw depth max. 6 mm

Without encoder



- 1 2 tags NFC 20 - 120; series 2.8 x 0.5
- 2 3 holes at 120° over Ø 26 mm; use self-tapping M2.2 screws; screw depth max. 6 mm